



15012 Eddie Drive
 Humble, Texas 77396
 281-441-2465
 800-456-2378
 281-441-2933 (fax)
 www.bestwashinc.com




ON-PREMISES LAUNDRY


RIGID-MOUNT SPECIFICATIONS




MYR55PN Shown




FRONT ELEVATION



BACK ELEVATION



SIDE ELEVATION



TOP ELEVATION

DIAGRAM KEY

- 1 Control Console
- 2 Loading Door
- 3 Electric Connection
- 4 Hot Water
- 5 Cold Water
- 6 Third Water
- 7 Drain
- 8 Steam Connection
- 9 Soap Dispenser
- 10 Automatic Liquid Soap Manifold
- 11 Electric Disconnect
- 12 USB
- 13 Fuses
- 14 Toe Panel
- 15 Stop Switch

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z					
26R	MM	1112	660	646	772	1139	994	336	435	431	1045	323	1800	181	1823	148	827	188	85	70	N/A	N/A	80	826	348	1832	288	1019	308	1064	1019
	MCB	43 3/4	26	27	38 3/4	45 3/4	39 3/4	14	16 1/4	17 1/4	41 3/4	8 1/4	39 3/4	4	48 3/4	3 1/4	36 3/4	8 1/4	3 1/4	2 1/4	N/A	N/A	2 1/4	32 3/4	14 1/4	40 3/4	11	48 3/4	12	41 3/4	48 3/4
26L	MM	1222	730	714	781	1184	1188	346	419	543	1156	225	1908	181	1933	146	1825	213	88	70	N/A	N/A	78	837	458	1148	371	1138	384	1155	1128
	MCB	48 3/4	39 3/4	28 3/4	31 1/4	48 3/4	43 3/4	13 3/4	16 1/4	21 3/4	43 3/4	8 1/4	43 3/4	4	44 3/4	3 1/4	48 3/4	8 1/4	3 1/4	2 1/4	N/A	N/A	2 1/4	35 3/4	18	44 3/4	14 1/4	44 3/4	13 1/4	45 3/4	44 3/4
36R	MM	1222	730	841	985	1308	1188	346	419	543	1156	225	1908	181	1933	146	1825	213	88	70	N/A	N/A	78	837	458	1148	371	1138	384	1155	1128
	MCB	48 3/4	39 3/4	32 3/4	38 3/4	54 3/4	43 3/4	13 3/4	16 1/4	21 3/4	43 3/4	8 1/4	43 3/4	4	44 3/4	3 1/4	48 3/4	8 1/4	3 1/4	2 1/4	N/A	N/A	2 1/4	35 3/4	18	44 3/4	14 1/4	44 3/4	13 1/4	45 3/4	44 3/4
46R	MM	1418	889	883	946	1470	1288	487	337	578	1343	289	1344	175	1321	175	1224	183	133	70	48	334	78	1899	482	1330	486	1387	439	1343	1318
	MCB	53 3/4	35	34 3/4	37 1/4	37 1/4	30 3/4	18 3/4	21 3/4	22 3/4	32 3/4	11 3/4	48	8 1/4	52	8 1/4	48 3/4	11 3/4	8 1/4	2 1/4	1 3/4	21	2 1/4	43 3/4	18 3/4	32 3/4	16	31 3/4	18 3/4	32 3/4	31 3/4
66R	MM	1418	889	1018	1089	1687	1288	487	337	578	1343	289	1344	175	1321	175	1224	183	133	70	48	334	78	1899	482	1330	486	1387	439	1343	1318
	MCB	53 3/4	35	48 3/4	42 3/4	62 3/4	30 3/4	18 3/4	21 3/4	22 3/4	32 3/4	11 3/4	48	8 1/4	52	8 1/4	48 3/4	11 3/4	8 1/4	2 1/4	1 3/4	21	2 1/4	43 3/4	18 3/4	32 3/4	16	31 3/4	18 3/4	32 3/4	31 3/4
66L	MM	1418	889	1882	1186	1680	1288	487	337	578	1343	289	1344	175	1321	175	1224	183	133	70	48	334	78	1899	482	1330	486	1387	439	1343	1318
	MCB	53 3/4	35	43	45 3/4	66 3/4	30 3/4	18 3/4	21 3/4	22 3/4	32 3/4	11 3/4	48	8 1/4	52	8 1/4	48 3/4	11 3/4	8 1/4	2 1/4	1 3/4	21	2 1/4	43 3/4	18 3/4	32 3/4	16	31 3/4	18 3/4	32 3/4	31 3/4



Three-Year Limited Warranty on Parts. For the first three (3) years from the date of purchase, when this commercial appliance is installed, maintained, and operated according to the instructions attached to or furnished with the product, Maytag® Commercial Laundry brand of Whirlpool Corporation (hereafter "Maytag") will pay for factory-specified parts or original equipment manufacturer parts to correct defects in materials or workmanship.

Fourth- and Fifth-Year Limited Warranty on Certain Parts. In the fourth year and fifth year from the date of purchase, Maytag will pay for the following washer parts: the outer shell, drum and shaft assembly, inner welded frame, and bearings and seals.

Visit maytagcommerciallaundry.com for warranty details.



15012 Eddie Drive
Humble, Texas 77396
281-441-2465
800-456-2378
281-441-2933 (fax)
www.bestwashinc.com



ON-PREMISES LAUNDRY

RIGID-MOUNT SPECIFICATIONS

MODEL	MYR20PN	MYR25PN	MYR30PN	MYR40PN	MYR55PN	MYR65PN
MOTOR						
Size – HP	0.5	0.75	1.0	1.5	2.0	2.0
CAPACITY						
Cylinder Volume – cu. ft. (liters)	2.58 (73)	3.55 (101)	4.61 (131)	6.04 (171)	8.14 (230)	9.25 (262)
Cylinder Diameter – in. (mm)	20.9 (530)	24.4 (620)	24.4 (620)	29.5 (750)	29.5 (750)	29.5 (750)
Cylinder Depth – in. (mm)	13.9 (352)	13.9 (352)	17.9 (454)	16.2 (411)	21.6 (548)	24.4 (621)
Dry Load Capacity – lb. (kg)	20 (9)	25 (11)	30 (14)	40 (18)	55 (25)	65 (30)
EXTRACT FORCE						
Maximum Extract Force (G-force)	200	200	200	200	200	200
CONNECTIVITY						
USB Programmability	Yes	Yes	Yes	Yes	Yes	Yes
Maytag Connect 360™ Technology* Ready	Yes	Yes	Yes	Yes	Yes	Yes
DIMENSIONS						
Depth – in. (mm)	27 (686)	28.5 (725)	33.1 (840)	34.8 (883)	40.1 (1,019)	43 (1092)
Width – in. (mm)	28 (680)	29.5 (750)	29.5 (750)	35.0 (890)	35.0 (890)	35.0 (890)
Height – in. (mm)	43.8 (1,112)	48.1 (1,222)	48.1 (1,222)	55.5 (1,410)	55.5 (1,410)	55.5 (1,410)
Door Opening – in. (mm)	12.9 (328)	16.1 (410)	16.1 (410)	18.1 (459)	18.1 (459)	18.1 (459)
CRATED DIMENSIONS						
Width – in. (mm)	27.8 (705)	31.5 (800)	31.5 (800)	37.0 (940)	37.0 (940)	37.0 (940)
Depth – in. (mm)	33.1 (841)	34.8 (880)	39.0 (991)	40.5 (1,029)	46.0 (1,169)	48.9 (1,242)
Height – in. (mm)	50.0 (1,270)	54.4 (1,381)	54.4 (1,381)	61.4 (1,560)	61.4 (1,560)	61.4 (1,560)
APPROXIMATE WEIGHT						
Uncrated – lb. (kg)	334 (151)	447 (203)	489 (222)	668 (312)	731 (332)	764 (347)
Crated – lb. (kg)	365 (166)	480 (218)	523 (237)	724 (328)	769 (349)	802 (364)
LOADING QUANTITY						
Full Truck (53' / 48')	63 / 57	56 / 50	48 / 42	34 / 30	34 / 30	34 / 30
40' HC Container	45	30	30	24	24	21
20' Container	22	14	14	12	12	10
ELECTRICAL CONNECTION OPTIONS (VOLTS/Hz/PHASE)						
W = 120 / 60 / 1 (no electrical heating)	Yes	Yes	Yes	No	No	No
T = 208 – 240 / 50 – 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes	Yes
S = 220 – 240 / 50 – 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes	Yes
V = 208 – 240 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes	Yes
N = 380 – 415 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes	Yes
R = 440 – 480 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes	Yes
WATER HEATING OPTIONS						
Hot/Cold Water Connections Only	Yes	Yes	Yes	Yes	Yes	Yes
Electrical Heating (size of heating elements, kW)	Yes (8)	Yes (8)	Yes (12)	Yes (16)	Yes (16)	Yes (18)
Electrical Heating, Optional Alternate Heating Element Size- kW	12	12	8	N/A	N/A	N/A
Steam Kit Option	No	No	No	Yes	Yes	Yes
WATER, CHEMICAL DISPENSING, DRAINS						
Number of Water Inlets	2	2	2	2	2	2
Optional Third Water Inlet	Yes	Yes	Yes	Yes	Yes	Yes
Inlet Sizes – in. (mm)	½ (13)	½ (13)	½ (13)	½ (13)	½ (13)	½ (19)
Operating Pressure – PSI (bar)	20 – 120 (1-8)	20 – 120 (1-8)	20 – 120 (1-8)	20 – 120 (1-8)	20 – 120 (1-8)	20 – 120 (1-8)
Number of Dispenser Compartments	4	4	4	4	4	4
External Chemical Connections, Number	10	10	10	10	10	10
Dump Valve Drain, Size – in. (mm)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)
Second Dump Valve Drain Option	No	No	No	No	Yes	Yes
Drain Pump Option	Yes	Yes	Yes	Yes	No	No
SOUND PRESSURE- dbA						
	<70	<70	<70	<70	<70	<70

*WiFi required. Features subject to change. Details and privacy info at connect360.maytag.com.
See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.
©/TM 2019 Maytag. All rights reserved. Printed in the U.S.A.