

ON-PREMISES LAUNDRY



15012 Eddie Drive
Humble, Texas 77396
281-441-2465
800-456-2378
281-441-2933 (fax)
www.bestwashinc.com



SOFT-MOUNT SPECIFICATIONS

| MODEL | MYS20PN | MYS30PN | MYS40PN | MYS55PN | MYS65PN |
|---|----------------|----------------|----------------|----------------|----------------|
| MOTOR | | | | | |
| Size – HP | 1.0 | 2.0 | 3.0 | 4.0 | 4.0 |
| CAPACITY | | | | | |
| Cylinder Volume – cu. ft. (liters) | 2.58 (73) | 4.61 (131) | 6.04 (171) | 8.14 (230) | 9.25 (262) |
| Cylinder Diameter – in. (mm) | 20.9 (530) | 24.4 (620) | 29.5 (750) | 29.5 (750) | 29.5 (750) |
| Cylinder Depth – in. (mm) | 13.9 (352) | 17.9 (454) | 16.2 (411) | 21.6 (548) | 24.4 (621) |
| Dry Load Capacity – lb. (kg) | 20 (9) | 30 (14) | 40 (18) | 55 (25) | 65 (30) |
| EXTRACT FORCE | | | | | |
| Maximum Extract Force (G-force) | 400 | 400 | 400 | 400 | 350 |
| CONNECTIVITY | | | | | |
| USB Programmability | Yes | Yes | Yes | Yes | Yes |
| Maytag Connect 360™ Technology* Ready | Yes | Yes | Yes | Yes | Yes |
| DIMENSIONS | | | | | |
| Depth – in. (mm) | 28.4 (721) | 34.3 (872) | 35.5 (901) | 40.8 (1,037) | 43.7 (1,110) |
| Width – in. (mm) | 28.0 (710) | 31.3 (795) | 38.2 (970) | 38.2 (970) | 38.2 (970) |
| Height – in. (mm) | 43.8 (1,112) | 48.1 (1,222) | 55.5 (1,410) | 55.5 (1,410) | 55.5 (1,410) |
| Door Opening – in. (mm) | 12.9 (328) | 16.1 (410) | 18.1 (459) | 18.1 (459) | 18.1 (459) |
| CRATED DIMENSIONS | | | | | |
| Width – in. (mm) | 29.8 (756) | 33.1 (841) | 39.5 (1,003) | 39.5 (1,003) | 39.5 (1,003) |
| Depth – in. (mm) | 33.4 (854) | 39.8 (1,010) | 41.0 (1,042) | 46.4 (1,178) | 49.3 (1,251) |
| Height – in. (mm) | 50.0 (1,270) | 54.4 (1,381) | 61.4 (1,560) | 61.4 (1,560) | 61.4 (1,560) |
| APPROXIMATE WEIGHT | | | | | |
| Uncrated – lb. (kg) | 415 (188) | 582 (264) | 851 (386) | 894 (406) | 944 (428) |
| Crated – lb. (kg) | 446 (202) | 616 (279) | 889 (403) | 933 (423) | 984 (446) |
| LOADING QUANTITY | | | | | |
| Full Truck (53' / 48') | 60 / 54 | 38 / 34 | 32 / 28 | 32 / 28 | 32 / 28 |
| 40' HC Container | 42 | 28 | 24 | 22 | 21 |
| 20' Container | 18 | 14 | 10 | 10 | 9 |
| ELECTRICAL CONNECTION OPTIONS (VOLTS/Hz/PHASE) | | | | | |
| W = 120 / 60 / 1 (no electrical heating) | Yes | Yes | No | No | No |
| T = 208 – 240 / 50 – 60 / 1 (no electrical heating) | Yes | Yes | Yes | Yes | Yes |
| S = 220 – 240 / 50 – 60 / 1 (no electrical heating) | Yes | Yes | Yes | Yes | Yes |
| V = 208 – 240 / 50 – 60 / 3 | Yes | Yes | Yes | Yes | Yes |
| N = 380 – 415 / 50 – 60 / 3 | Yes | Yes | Yes | Yes | Yes |
| R = 440 – 480 / 50 – 60 / 3 | Yes | Yes | Yes | Yes | Yes |
| WATER HEATING OPTIONS | | | | | |
| Hot/Cold Water Connections Only | Yes | Yes | Yes | Yes | Yes |
| Electrical Heating (size of heating elements, kW) | Yes (8) | Yes (12) | Yes (16) | Yes (18) | Yes (18) |
| Electrical Heating, Optional Alternate Heating Element Size- kW | 12 | 8 | N/A | N/A | N/A |
| Steam Kit Option | No | No | Yes | Yes | Yes |
| WATER, CHEMICAL DISPENSING, DRAINS | | | | | |
| Number of Water Inlets | 2 | 2 | 2 | 2 | 2 |
| Optional Third Water Inlet | Yes | Yes | Yes | Yes | Yes |
| Inlet Sizes – in. (mm) | ½ (13) | ½ (13) | ½ (13) | ½ (13) | ¾ (19) |
| Operating Pressure – PSI (bar) | 20 – 120 (1-8) | 20 – 120 (1-8) | 20 – 120 (1-8) | 20 – 120 (1-8) | 20 – 120 (1-8) |
| Number of Dispenser Compartments | 4 | 4 | 4 | 4 | 4 |
| External Chemical Connections, Number | 10 | 10 | 10 | 10 | 10 |
| Dump Valve Drain, Size – in. (mm) | Yes, 3 (76) | Yes, 3 (76) | Yes, 3 (76) | Yes, 3 (76) | Yes, 3 (76) |
| Second Dump Valve Drain Option | No | No | No | Yes | Yes |
| Drain Pump Option | Yes | Yes | Yes | No | No |
| SOUND PRESSURE-dbA | | | | | |
| | <70 | <70 | <70 | <70 | <70 |

*WiFi required. Features subject to change. Details and privacy info at connect360.maytag.com.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

®/™ ©2019 Maytag. All rights reserved. Printed in the U.S.A.