



15012 Eddie Drive
Humble, Texas 77396
281-441-2465
800-456-2378
281-441-2933 (fax)
www.bestwashinc.com

VENDED LAUNDRY




COMMERCIAL LAUNDRY DISTRIBUTOR


RIGID-MOUNT SPECIFICATIONS




MYR55PD Shown




FRONT ELEVATION



BACK ELEVATION



SIDE ELEVATION



TOP ELEVATION

DIAGRAM KEY

- 1 Control Console
- 2 Loading Door
- 3 Electric Connection
- 4 Hot Water
- 5 Cold Water
- 6 Third Water
- 7 Drain
- 8 Steam Connection
- 9 Soap Dispenser
- 10 Automatic Liquid Soap Manifold
- 11 Electric Disconnect
- 12 USB
- 13 Fuses
- 14 Toe Panel
- 15 Payment Mech. Location

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z					
241	MM	1112	680	646	772	1139	954	534	435	431	1845	235	1800	181	1003	146	927	168	85	70	N/A	N/A	80	816	368	1002	280	1078	305	1004	1019
	INCH	43 3/4	26	27	30 3/4	45 1/8	38 3/8	14	16 3/4	17 3/8	71 3/8	9 1/8	70 7/8	7 1/8	39 3/8	5 7/8	3 3/8	3 1/2	2 3/4	N/A	N/A	3 1/8	32 1/2	14 1/2	48 1/2	11	40 1/2	12	41 1/2	40 7/8	
251	MM	1322	730	714	781	1254	1108	146	489	543	1956	235	1908	181	1130	146	1035	213	90	70	N/A	N/A	70	857	408	1140	371	1130	394	1155	1158
	INCH	48 1/2	28 3/4	28 1/2	31 1/8	49 1/8	43 5/8	13 1/8	19 1/8	21 3/8	77 1/8	9 1/8	74 3/8	7 1/8	44 1/2	5 7/8	40 7/8	8 3/8	3 3/4	2 3/4	N/A	N/A	2 3/4	33 3/8	16	44 1/2	14 1/2	44 1/2	15 1/2	45 1/2	44 7/8
341	MM	1322	730	641	685	1270	1108	146	489	543	1956	235	1908	181	1130	146	1035	213	90	70	N/A	N/A	70	857	408	1140	371	1130	394	1155	1158
	INCH	48 1/2	28 3/4	25 1/4	26 3/4	50 1/8	43 5/8	13 1/8	19 1/8	21 3/8	77 1/8	9 1/8	74 3/8	7 1/8	44 1/2	5 7/8	40 7/8	8 3/8	3 3/4	2 3/4	N/A	N/A	2 3/4	33 3/8	16	44 1/2	14 1/2	44 1/2	15 1/2	45 1/2	44 7/8
441	MM	1418	689	650	646	1470	1288	467	537	578	1343	289	1344	175	1321	175	1224	283	133	70	45	534	70	1085	482	1330	406	1317	428	1343	1348
	INCH	55 7/8	26	25 5/8	27 1/8	57 7/8	50 3/4	18 3/8	21 1/8	22 3/4	52 1/4	11 1/4	52	6 3/4	52	6 3/4	48 1/4	11 1/8	5 1/8	2 3/4	1 3/4	21	2 3/4	42 1/2	19 1/4	52 1/4	16	51 1/4	16 1/2	52 1/4	51 1/4
541	MM	1418	689	1018	1800	1687	1288	467	537	578	1343	289	1344	175	1321	175	1224	283	133	70	45	534	70	1085	482	1330	406	1317	428	1343	1348
	INCH	55 7/8	26	40 1/4	70 3/4	66 3/8	50 3/4	18 3/8	21 1/8	22 3/4	52 1/4	11 1/4	48	6 3/4	52	6 3/4	48 1/4	11 1/8	5 1/8	2 3/4	1 3/4	21	2 3/4	42 1/2	19 1/4	52 1/4	16	51 1/4	16 1/2	52 1/4	51 1/4
641	MM	1418	689	1182	1186	1680	1288	467	537	578	1343	289	1344	175	1321	175	1224	283	133	70	45	534	70	1085	482	1330	406	1317	428	1343	1348
	INCH	55 7/8	26	43	42 3/4	66 1/4	50 3/4	18 3/8	21 1/8	22 3/4	52 1/4	11 1/4	48	6 3/4	52	6 3/4	48 1/4	11 1/8	5 1/8	2 3/4	1 3/4	21	2 3/4	42 1/2	19 1/4	52 1/4	16	51 1/4	16 1/2	52 1/4	51 1/4



Five-Year Limited Warranty on Parts (Parts Only – Labor Not Included). For the first five years from the original date of purchase, when this commercial appliance is installed, operated, and maintained according to the instructions attached to or furnished with the product, Maytag® Commercial Laundry brand of Whirlpool Corporation (hereafter "Maytag") will pay for factory-specified replacement parts to correct defects in materials or workmanship that existed when this commercial appliance was purchased. This limited warranty does not include labor.

Sixth- Through Tenth-Year Limited Warranty (Certain Component Parts Only). In the Sixth through Tenth years from the date of original purchase, when this commercial appliance is installed, operated, and maintained according to instructions attached to or furnished with the product, Maytag will pay for factory-specified replacement parts for the following components to correct non-cosmetic defects in materials or workmanship in the parts that prevent function of the product and that existed when this commercial appliance was purchased. This is a limited 10-year warranty on the named parts only and does not include labor: outer shell, drum and shaft assembly, inner welded frame, and bearings and seals.

Visit maytagcommerciallaundry.com for warranty details.



15012 Eddie Drive
 Humble, Texas 77396
 281-441-2465
 800-456-2378
 281-441-2933 (fax)
 www.bestwashinc.com

VENDED LAUNDRY



RIGID-MOUNT SPECIFICATIONS

MODEL	MYR20PD	MYR25PD	MYR30PD	MYR40PD	MYR55PD	MYR65PD
MOTOR						
Size — HP	0.5	0.75	1.0	1.5	2.0	2.0
CAPACITY						
Cylinder Volume — cu ft. (liters)	2.58 (73)	3.55 (101)	4.61 (131)	6.04 (171)	8.14 (230)	9.25 (262)
Cylinder Diameter — in. (mm)	20.9 (530)	24.4 (620)	24.4 (620)	29.5 (750)	29.5 (750)	29.5 (750)
Cylinder Depth — in. (mm)	13.9 (352)	13.9 (352)	17.9 (454)	16.2 (411)	21.6 (548)	24.4 (621)
Dry Load Capacity — lb. (kg)	20 (9)	25 (11)	30 (14)	40 (18)	55 (25)	65 (30)
EXTRACT FORCE						
Maximum Extract Force (G-force)	200	200	200	200	200	200
CONNECTIVITY						
USB Programmability	Yes	Yes	Yes	Yes	Yes	Yes
Maytag Connect 360™ Technology* Ready	Yes	Yes	Yes	Yes	Yes	Yes
DIMENSIONS						
Depth — in. (mm)	27 (686)	28.5 (724)	33.1 (841)	34.6 (883)	40.1 (1,019)	43 (1092)
Width — in. (mm)	26 (660)	29.5 (750)	29.5 (750)	35.0 (890)	35.0 (890)	35.0 (890)
Height — in. (mm)	43.8 (1,112)	48.1 (1,222)	48.1 (1,222)	55.5 (1,410)	55.5 (1,410)	55.5 (1,410)
Door Opening — in. (mm)	12.9 (328)	16.1 (410)	16.1 (410)	18.1 (459)	18.1 (459)	18.1 (459)
CRATED DIMENSIONS						
Width — in. (mm)	27.8 (705)	31.5 (800)	31.5 (800)	37.0 (940)	37.0 (940)	37.0 (940)
Depth — in. (mm)	33.1 (841)	34.6 (880)	39.0 (991)	40.5 (1,029)	46.0 (1,169)	48.9 (1,242)
Height — in. (mm)	50.0 (1,270)	54.4 (1,381)	54.4 (1,381)	61.4 (1,560)	61.4 (1,560)	61.4 (1,560)
APPROXIMATE WEIGHT						
Uncrated — lb. (kg)	334 (151)	447 (203)	489 (222)	688 (312)	731 (332)	764 (347)
Crated — lb. (kg)	365 (166)	480 (218)	523 (237)	724 (328)	769 (349)	802 (364)
LOADING QUANTITY						
Full Truck (53' / 48')	63 / 57	56 / 50	48 / 42	34 / 30	34 / 30	34 / 30
40' HC Container	45	30	30	24	24	21
20' Container	22	14	14	12	12	10
ELECTRICAL CONNECTION OPTIONS (VOLTS / Hz / PHASE)						
W = 120 / 60 / 1 (no electrical heating)	Yes	Yes	Yes	No	No	No
T = 208 – 240 / 50 – 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes	Yes
S = 220 – 240 / 50 – 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes	Yes
V = 208 – 240 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes	Yes
N = 380 – 415 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes	Yes
R = 440 – 480 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes	Yes
WATER HEATING OPTIONS						
Hot/Cold Water Connections Only	Yes	Yes	Yes	Yes	Yes	Yes
Electrical Heating (size of heating elements, kW)	Yes (8)	Yes (8)	Yes (12)	Yes (16)	Yes (16)	Yes (18)
Electrical Heating, Optional Alternate Heating Element size- kW	12	12	8	N/A	N/A	N/A
Steam Kit Option	No	No	No	Yes	Yes	Yes
WATER, CHEMICAL DISPENSING, DRAINS						
Number of Water Inlets	2	2	2	2	2	2
Optional Third Water Inlet	Yes	Yes	Yes	Yes	Yes	Yes
Inlet Sizes — in. (mm)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)	3/4 (19)
Operating Pressure — PSI (bar)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)
Number of Dispenser Compartments	4	4	4	4	4	4
External Chemical Connections, Number	10	10	10	10	10	10
Dump Valve Drain, Size in. (mm)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)
Second Dump Valve Drain Option	No	No	No	No	Yes	Yes
Drain Pump Option	Yes	Yes	Yes	Yes	No	No
SOUND PRESSURE – dbA						
	<70	<70	<70	<70	<70	<70

*WiFi required. Features subject to change. Details and privacy info at connect360.maytag.com.
 See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.
 ©/TM 2019 Maytag. All rights reserved. Printed in the U.S.A.