



15012 Eddie Drive
Humble, Texas 77396
281-441-2465
800-456-2378
281-441-2933 (fax)
www.bestwashinc.com




VENDED LAUNDRY


SOFT-MOUNT SPECIFICATIONS




MYS20PD Shown




FRONT ELEVATION



BACK ELEVATION



SIDE ELEVATION



TOP ELEVATION

DIAGRAM KEY

- 1 Control Console
- 2 Loading Door
- 3 Electric Connection
- 4 Hot Water
- 5 Cold Water
- 6 Third Water
- 7 Drain
- 8 Steam Connection
- 9 Soap Dispenser
- 10 Automatic Liquid Soap Manifold
- 11 Electric Disconnect
- 12 USB
- 13 Fuses
- 14 Toe Panel
- 15 Payment Mech. Location

		A	B	C	D	E	F	G	H	I1	I2	J1	J2	K1	K2	L1	L2	M1	M2	N1	N2	O1	O2	P1	P2	Q1	Q2	R1	R2	R3	
215	NM	1112	711	720	781	1170	950	353	433	302	1048	215	1003	101	1028	146	601	229	90	78	N/A	N/A	70	826	419	1335	330	1025	335	1048	1003
	INCH	43 3/4	28	28 1/2	30 3/4	46	38 1/4	13 7/8	16 3/4	19 1/4	41 1/4	8 1/2	39 1/4	4	40 1/2	5 3/4	23 3/4	9	3 1/2	3 1/4	N/A	N/A	2 3/4	32 1/2	16 1/2	40 1/4	13	42 1/4	14	41 1/4	40 3/4
315	NM	1221	794	872	838	1489	1103	349	428	388	1189	225	1112	101	1137	148	1041	228	80	78	N/A	N/A	78	836	582	1148	416	1138	441	1189	1138
	INCH	48 1/4	31 1/4	34 1/4	32 3/4	58 1/4	43 1/4	13 3/4	16 3/4	32 3/4	46 3/4	8 3/4	43 3/4	4	44 1/4	5 3/4	41	8	3 1/4	3 1/4	N/A	N/A	2 3/4	33 1/2	18 1/4	43 1/4	16 1/4	44 1/4	17 1/4	45 3/4	44 1/4
415	NM	1410	878	981	954	1471	1298	478	548	497	1347	300	1228	173	1324	173	1238	278	111	78	63	898	78	1894	572	1334	486	1221	511	1347	1321
	INCH	55 1/4	34 1/4	38 1/4	37 1/4	58 1/4	51 1/4	18 3/4	21 1/4	21 3/4	53	11 3/4	48 3/4	6 3/4	52 1/4	6 3/4	48 3/4	10 3/4	4 1/4	3 1/4	2 1/4	2 1/4	37 1/4	2 3/4	43 1/4	22 1/4	52 1/4	19 1/4	51	51 1/4	52
615	NM	1410	878	1008	1108	1634	1298	478	548	497	1347	300	1228	173	1324	173	1238	278	111	78	63	898	78	1894	572	1334	486	1221	511	1347	1321
	INCH	55 1/4	34 1/4	40 1/4	43 1/4	64	51 1/4	18 3/4	21 1/4	21 3/4	53	11 3/4	48 3/4	6 3/4	52 1/4	6 3/4	48 3/4	10 3/4	4 1/4	3 1/4	2 1/4	2 1/4	37 1/4	2 3/4	43 1/4	22 1/4	52 1/4	19 1/4	51	51 1/4	52
815	NM	1410	878	1110	1172	1687	1298	478	548	497	1347	300	1228	173	1324	173	1238	278	111	78	63	898	78	1894	572	1334	486	1221	511	1347	1321
	INCH	55 1/4	34 1/4	43 1/4	46 1/4	66 1/4	51 1/4	18 3/4	21 1/4	21 3/4	53	11 3/4	48 3/4	6 3/4	52 1/4	6 3/4	48 3/4	10 3/4	4 1/4	3 1/4	2 1/4	2 1/4	37 1/4	2 3/4	43 1/4	22 1/4	52 1/4	19 1/4	51	51 1/4	52



Five-Year Limited Warranty on Parts (Parts Only – Labor Not Included). For the first five years from the original date of purchase, when this commercial appliance is installed, operated, and maintained according to the instructions attached to or furnished with the product, Maytag® Commercial Laundry brand of Whirlpool Corporation (hereafter "Maytag") will pay for factory-specified replacement parts to correct defects in materials or workmanship that existed when this commercial appliance was purchased. This limited warranty does not include labor.

Sixth- Through Tenth-Year Limited Warranty (Certain Component Parts Only). In the Sixth through Tenth years from the date of original purchase, when this commercial appliance is installed, operated, and maintained according to instructions attached to or furnished with the product, Maytag will pay for factory-specified replacement parts for the following components to correct non-cosmetic defects in materials or workmanship in the parts that prevent function of the product and that existed when this commercial appliance was purchased. This is a limited 10-year warranty on the named parts only and does not include labor: outer shell, drum and shaft assembly, inner welded frame, and bearings and seals.

Visit maytagcommerciallaundry.com for warranty details.



15012 Eddie Drive
 Humble, Texas 77396
 281-441-2465
 800-456-2378
 281-441-2933 (fax)
 www.bestwashinc.com



VENDED LAUNDRY

SOFT-MOUNT SPECIFICATIONS

MODEL	MYS20PD	MYS30PD	MYS40PD	MYS55PD	MYS65PD
MOTOR					
Size — HP	1.0	2.0	3.0	4.0	4.0
CAPACITY					
Cylinder Volume — cu. ft. (liters)	2.58 (73)	4.61 (131)	6.04 (171)	8.14 (230)	9.25 (262)
Cylinder Diameter — in. (mm)	20.9 (530)	24.4 (620)	29.5 (750)	29.5 (750)	29.5 (750)
Cylinder Depth — in. (mm)	13.9 (352)	17.9 (454)	18.2 (411)	21.8 (548)	24.4 (621)
Dry Load Capacity — lb. (kg)	20 (9)	30 (14)	40 (18)	55 (25)	65 (30)
EXTRACT FORCE					
Maximum Extract Force (G-force)	400	400	400	400	350
CONNECTIVITY					
USB Programmability	Yes	Yes	Yes	Yes	Yes
Maytag Connect 360™ Technology* Ready	Yes	Yes	Yes	Yes	Yes
DIMENSIONS					
Depth — in. (mm)	26.4 (720)	34.3 (872)	35.5 (901)	40.8 (1,036)	43.7 (1,110)
Width — in. (mm)	28.0 (711)	31.3 (794)	38.2 (970)	38.2 (970)	38.2 (970)
Height — in. (mm)	43.8 (1,112)	48.1 (1,222)	55.5 (1,410)	55.5 (1,410)	55.5 (1,410)
Door opening — in. (mm)	12.9 (328)	18.1 (410)	18.1 (459)	18.1 (459)	18.1 (459)
CRATED DIMENSIONS					
Width — in. (mm)	29.8 (756)	33.1 (841)	39.5 (1,003)	39.5 (1,003)	39.5 (1,003)
Depth — in. (mm)	33.6 (854)	39.8 (1,010)	41.0 (1,042)	46.4 (1,178)	49.3 (1,251)
Height — in. (mm)	50.0 (1,270)	54.4 (1,381)	61.4 (1,560)	61.4 (1,560)	61.4 (1,560)
APPROXIMATE WEIGHT					
Uncrated — lb. (kg)	415 (188)	582 (264)	651 (386)	894 (408)	944 (428)
Crated — lb. (kg)	448 (202)	616 (279)	889 (403)	933 (423)	984 (446)
LOADING QUANTITY					
Full Truck (53' / 48')	60 / 54	38 / 34	32 / 28	32 / 28	32 / 28
40' HC Container	42	28	24	22	21
20' Container	18	14	10	10	9
ELECTRICAL CONNECTION OPTIONS (VOLTS / Hz / PHASE)					
W = 120 / 60 / 1 (no electrical heating)	Yes	Yes	No	No	No
T = 208 – 240 / 50 – 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes
S = 220 – 240 / 50 – 60 / 1 (no electrical heating)	Yes	Yes	Yes	Yes	Yes
V = 208 – 240 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes
N = 380 – 415 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes
R = 440 – 480 / 50 – 60 / 3	Yes	Yes	Yes	Yes	Yes
WATER HEATING OPTIONS					
Hot/Cold Water Connections Only	Yes	Yes	Yes	Yes	Yes
Electrical Heating (size of heating elements, kW)	Yes (8)	Yes (12)	Yes (18)	Yes (18)	Yes (18)
Electrical Heating, Optional Alternate Heating Element Size- kW	12	8	N/A	N/A	N/A
Steam Kit Option	No	No	Yes	Yes	Yes
WATER, CHEMICAL DISPENSING, DRAINS					
Number of Water Inlets	2	2	2	2	2
Optional Third Water Inlet	Yes	Yes	Yes	Yes	Yes
Inlet Sizes — in. (mm)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)	3/4 (19)
Operating Pressure — PSI (bar)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)	20-120 (1-8)
Number of Dispenser Compartments	4	4	4	4	4
External Chemical Connections, Number	10	10	10	10	10
Dump Valve Drain, Size in. (mm)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)	Yes, 3 (76)
Second Dump Valve Drain Option	No	No	No	Yes	Yes
Drain Pump Option	Yes	Yes	Yes	No	No
SOUND PRESSURE — dbA					
	<70	<70	<70	<70	<70

*WiFi required. Features subject to change. Details and privacy info at connect360.maytag.com.
 See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.
 ®/™ ©2019 Maytag. All rights reserved. Printed in the U.S.A.