

MAYTAG MULTI-LOAD WASHERS

SOFT MOUNT • NON VEND (OPL)
MWSxxPN



NON VEND (OPL)
MWS55PNATS pictured

In commercial laundry, the right tools, shaped by trusted collaboration, build lasting confidence. With an all-new multi-load washer lineup that delivers capacities up to 85 pounds, Maytag Commercial Laundry now offers an expanded, end-to-end solution. Together with our multi-load dryer lines, these machines give operators what they've asked for: reliable, durable equipment built to satisfy market demands.

STANDARD FEATURES

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large doors open to 180° angle
- Choice of liquid or powder detergent in 5-compartment front soap dispenser equipped for automatic soap dosing
- Drum, tub, and front panel made of robust and durable high-quality AISI 304 stainless steel
- Ceramic-coated shaft sleeve
- USB front connection
- Flexible & fully programmable control with advanced 7" color display
- On-screen illustrated troubleshooting guide
- Balancing accelerometer
- Large 3" drain valve
- Electric heating (Int'l models only)
- 360G extraction speed
- Second drain valve (85-lb models only)

MULTI-LOAD FRONT-LOAD WASHERS NON VEND (OPL) — NAR MODELS	
MWS25PNATS	MWS55PNATS
MWS35PNATS	MWS65PNATS
MWS45PNATS	MWS85PNAVS

MULTI-LOAD FRONT-LOAD WASHERS NON VEND (OPL) — INTERNATIONAL MODELS	
MWS25PNARS	MWSS55PNARS
MWS35PNARS	MWS65PNARS
MWS45PNARS	MWS85PNARS



See maytagcommerciallaundry.com for warranty details.

VISIT MAYTAGCOMMERCIALLAUNDRY.COM FOR MORE INFORMATION.

MAYTAG MULTI-LOAD WASHERS

SOFT MOUNT • NON VEND (OPL)
MWSxxPN



NAR MODEL INTERNATIONAL MODEL	MWS25PNATS MWS25PNARS	MWS35PNATS MWS35PNARS	MWS45PNATS MWS45PNARS	MWS55PNATS MWS55PNARS	MWS65PNATS MWS65PNARS	MWS85PNATS MWS85PNARS
CAPACITY						
Rated Capacity — lb (kg)	25 (11.4)	35 (15.9)	45 (20.5)	55 (25.0)	65 (29.5)	85 (38.6)
Extraction (G-Force)	360	360	360	360	360	360
Drum Diameter — in (mm)	24.8 (630)	24.8 (630)	24.8 (630)	27.6 (701)	27.6 (701)	35.4 (899)
Drum Depth — in (mm)	13.0 (330)	19.3 (490)	22.8 (579)	24.8 (630)	28.3 (719)	22.6 (574)
Drum Volume — cu ft (L)	3.6 (102)	5.4 (153)	6.4 (181)	8.5 (241)	9.8 (278)	12.9 (365)
DIMENSIONS						
Unpacked Width — in (mm)	34.6 (879)	34.6 (879)	34.6 (879)	38.4 (975)	38.4 (975)	46.2 (1,173)
Unpacked Depth — in (mm)	38.4 (975)	44.7 (1,135)	48.3 (1,227)	50.0 (1,270)	53.5 (1,359)	55.3 (1,405)
Unpacked Height — in (mm)	59.1 (1,501)	59.1 (1,501)	59.1 (1,501)	61.6 (1,565)	62.6 (1,590)	66.5 (1,689)
Packed Width — in (mm)	36.6 (930)	36.6 (930)	36.6 (930)	40.2 (1,021)	40.2 (1,021)	48.8 (1,240)
Packed Depth — in (mm)	40.9 (1,039)	47.2 (1,199)	51.2 (1,300)	53.1 (1,349)	56.7 (1,440)	58.3 (1,481)
Packed Height — in (mm)	61.0 (1,549)	61.0 (1,549)	61.0 (1,549)	63.8 (1,621)	63.8 (1,621)	68.5 (1,740)
APPROXIMATE WEIGHT						
Net Weight — lb (kg)	964 (437.3)	1,019 (462.2)	1,047 (474.9)	1,562 (708.5)	1,760 (798.3)	2,255 (1,022.9)
Shipping Weight — lb (kg)	1,000 (453.6)	1,060 (480.8)	1,090 (494.4)	1,605 (728.0)	1,804 (818.3)	2,300 (1,043.3)
ELECTRICAL REQUIREMENTS						
Voltage — NAR	208-240V	208-240V	208-240V	208-240V	208-240V	208-240V
Voltage — International	380-415V	380-415V	380-415V	380-415V	380-415V	380-415V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power Supply — NAR	1-Phase	1-Phase	1-Phase	1-Phase	1-Phase	3-Phase
Power Supply — International	3-Phase, 4W	3-Phase, 4W	3-Phase, 4W	3-Phase, 4W	3-Phase, 4W	3-Phase, 4W
WATER MEASUREMENTS						
Water Consumption COLD — Gal (L)/cycle	10.3 (39)	15.3 (58)	18 (68)	20.6 (78)	23.5 (89)	23.5 (89)
Water Consumption HOT — Gal (L)/cycle	11.1 (42)	16.4 (62)	19.3 (73)	19.3 (73)	22.7 (86)	26.2 (99)
Water Consumption TOTAL — Gal (L)/cycle	21.4 (81)	31.7 (120)	37.2 (141)	39.9 (151)	46.2 (175)	49.7 (188)
Drain Valve (Outer Diameter) — in (mm)	3 (76.2)	3 (76.2)	3 (76.2)	3 (76.2)	3 (76.2)	3 (76.2)